




Data Sheet PI/P M 20



| | |
|---|--|
| UL Certification | File Nr. E502533 for category QEUY2/8 for use below 1000V File Nr. E502534 for category DLAR2/8 for use above 1000V |
| Operating Temperature | °C: - 40° + 130° |
| Fire reaction | UL94-V0 File Nr. E205214 HL2 according to the EN45545-2 |
| Material Insulating Parts | Polyester material reinforced with fiberglass BMC RF 3/20 |
| Material Nr. 1 Central Bolt, Nr. 1 Nut and Nr. 3 washers | Nichel-plated brass |
| Material Nr. 2 Nuts and Nr. 2 toothed washers | Galvanized steel |
| F | M 20 |
| Tightening torque | 26 Nm |
| H | 44 mm |
| L | 155 mm |
| A | 25 mm |
| Ø B | 54 mm |
| C max | 8 mm |
| Ø 1 | 6 mm |
| Ø 2 | 30,5 mm |
| In rated range | 450 A |
| Operating voltage | 2000 V |
| Test Voltage | 8 KV |
| Package | 5 pcs |
| Weight of package | 3,80 kgs |

ERIM SRL

Via Bovisasca 24/26 - 20026 - Novate Milanese (MI) - Italy

Tel. (+39) 02/39100533 – Fax. (+39) 02/49698772 – info@erim.it – www.erim.it

P.I./C.F. IT 01803920154 – R.E.A. MI N. 875797 – Reg. Imp. N. 158589 Trib. MI

Cod. SDI SUBM70N