




Data Sheet PI/P M 4



UL Certification	File Nr. E502533 for category QEUY2/8 for use below 1000V
Operating Temperature	°C: - 40° + 130°
Fire reaction	UL94-V0 File Nr. E205214
	HL2 according to the EN45545-2
Material Insulating Parts	Polyester material reinforced with fiberglass BMC RF 3/20
Material Nr. 1 Central Bolt, Nr. 1 Nut and Nr. 3 washers	Nichel-plated brass
Material Nr. 2 Nuts and Nr. 2 toothed washers	Galvanized steel
F	M 4
Tightening torque	3 Nm
H	12,5 mm
L	50 mm
A	10 mm
Ø B	15 mm
C max	3 mm
Ø 1	2,5 mm
Ø 2	8,5 mm
In rated range	25 A
Operating voltage	600 V
Test Voltage	4 KV
Package	60 pcs
Weight of package	1,00 kgs

ERIM SRL

Via Bovisasca 24/26 - 20026 - Novate Milanese (MI) - Italy

Tel. (+39) 02/39100533 – Fax. (+39) 02/49698772 – info@erim.it – www.erim.it

P.I./C.F. IT 01803920154 – R.E.A. MI N. 875797 – Reg. Imp. N. 158589 Trib. MI

Cod. SDI SUBM70N