




Data Sheet PI/P M 6



UL Certification	File Nr. E502533 for category QEUY2/8 for use below 1000V
Operating Temperature	°C: - 40° + 130°
Fire reaction	UL94-V0 File Nr. E205214
	HL2 according to the EN45545-2
Material Insulating Parts	Polyester material reinforced with fiberglass BMC RF 3/20
Material Nr. 1 Central Bolt, Nr. 1 Nut and Nr. 3 washers	Nichel-plated brass
Material Nr. 2 Nuts and Nr. 2 toothed washers	Galvanized steel
F	M 6
Tightening torque	5 Nm
H	17 mm
L	65 mm
A	12 mm
Ø B	22 mm
C max	5 mm
Ø 1	3,5 mm
Ø 2	12,5 mm
In rated range	50 A
Operating voltage	1000 V
Test Voltage	6 KV
Package	40 pcs
Weight of package	1,60 kgs

ERIM SRL

Via Bovisasca 24/26 - 20026 - Novate Milanese (MI) - Italy

Tel. (+39) 02/39100533 – Fax. (+39) 02/49698772 – info@erim.it – www.erim.it

P.I./C.F. IT 01803920154 – R.E.A. MI N. 875797 – Reg. Imp. N. 158589 Trib. MI

Cod. SDI SUBM70N