




Data Sheet I2IC1000



UL Certification	File Nr. E502533 for category QEU2/8 for use below 1000V
	File Nr. E502534 for category DLAR2/8 for use above 1000V
Material	Polyester material reinforced with fiberglass BMC RF 3/20
Operating Temperature	°C: - 40° + 130°
Fire reaction	UL94-V0 File Nr. E205214
	HL2 according to the EN45545-2
Thread Material	Galvanized Steel
A	52 mm
E	M10 : 13 mm / M12 : 13 mm / M16 : 17 mm
Tightening Torque	M10 : 24 Nm / M12 : 36 Nm / M16 : 50 Nm
C	100 mm
D	50 mm
Operating Voltage	5000 V
A.C. surface flashover voltage	50 KV
A.C. internal flashover voltage	40 KV
Tensile stress	1.950 DN
Cantilever stress	980 DN
Compressive stress	14.700 DN
Twisting stress	10 DN x mm
Package	80 pcs
Weight of package	M 10 29,10 kgs / M 12 28,70 Kgs. / M 16 30,30 Kgs.

ERIM SRL

Via Bovisasca 24/26 - 20026 - Novate Milanese (MI) - Italy

Tel. (+39) 02/39100533 – Fax. (+39) 02/49698772 – info@erim.it – www.erim.it

P.I./C.F. IT 01803920154 – R.E.A. MI N. 875797 – Reg. Imp. N. 158589 Trib. MI

Cod. SDI SUBM70N