




Data Sheet CO/P 30



UL Certification	File Nr. E502533 for category QEUY2/8 for use below 1000V
Material	Polyester material reinforced with fiberglass BMC RF 3/20
Operating Temperature	°C: - 40° + 130°
Fire reaction	UL94-V0 File Nr. E205214
	HL2 according to the EN45545-2
Thread Material	Galvanized Steel
H	30 mm
E	M4, M5, M6 and M8 : 8 mm
Tightening Torque	M4 : 2 Nm / M5 : 8 Nm / M6 : 12 Nm / M8 : 16 Nm
Operating Voltage	600 V
A.C. surface flashover voltage	5 KV
A.C. internal flashover voltage	15 KV
Tensile stress	400 DN
Cantilever stress	200 DN
Compressive stress	2.100 DN
Twisting stress	1 - 2 DN x mm
Package	140 pcs
Weight of package	4,20 kgs

ERIM SRL

Via Bovisasca 24/26 - 20026 - Novate Milanese (MI) - Italy

Tel. (+39) 02/39100533 – Fax. (+39) 02/49698772 – info@erim.it – www.erim.it

P.I./C.F. IT 01803920154 – R.E.A. MI N. 875797 – Reg. Imp. N. 158589 Trib. MI

Cod. SDI SUBM70N