




Data Sheet CS/P 30



UL Certification	File Nr. E502533 for category QEUY2/8 for use below 1000V File Nr. E502534 for category DLAR2/8 for use above 1000V
Material	Polyester material reinforced with fiberglass BMC RF 3/20
Operating Temperature	°C: - 40° + 130°
Fire reaction	UL94-V0 File Nr. E205214 HL2 according to the EN45545-2
Thread Material	Galvanized Steel
H	30 mm
E	M6 : 9 mm / M8 : 8 mm / M 10 : 7 mm
Tightening Torque	M6 : 10 Nm / M8 : 22 Nm / M 10 : 24 Nm
Operating Voltage	750 V
A.C. surface flashover voltage	8 KV
A.C. internal flashover voltage	20 KV
Tensile stress	900 DN
Cantilever stress	450 DN
Compressive stress	4.100 DN
Twisting stress	1,3-2,6 DN x mm
Package	80 pcs
Weight of package	4,80 kgs

ERIM SRL

Via Bovisasca 24/26 - 20026 - Novate Milanese (MI) - Italy
 Tel. (+39) 02/39100533 – Fax. (+39) 02/49698772 – info@erim.it – www.erim.it
 P.I./C.F. IT 01803920154 – R.E.A. MI N. 875797 – Reg. Imp. N. 158589 Trib. MI
 Cod. SDI SUBM70N